



**2011 SPECIFICATIONS**

PRODUCT NAME	Pro Zoom® 60	Pro Zoom® 54	Pro Zoom® 52 Stand-On	Max Zoom® 60	Max Zoom® 52	Max Zoom® 48
MODEL NUMBER	992807	992806	994806	991087	991086	991085
ENGINE	Kawasaki® FX	Kawasaki® FX	Kawasaki® FX	Kawasaki® FR Twin	Kawasaki® FR Twin	Kawasaki® FR Twin
HORSEPOWER*	27 hp	27 hp	20 hp	26 hp	24 hp	24 hp
DISPLACEMENT (cc)	852 cc	852 cc	603 cc	726 cc	726 cc	726 cc
DRIVE SYSTEM	Hydrostatic Hydro-Gear® 16cc Pump with Parker® 17.4 c.i. Wheel Motors	Hydrostatic Hydro-Gear® 16cc Pump with Parker® 17.4 c.i. Wheel Motors	Pumps and Motors 10 CC	Hydro-Gear® ZT-3100 Transaxles	Hydro-Gear® ZT-3100 Transaxles	Hydro-Gear® ZT-3100 Transaxles
FUEL CAPACITY GALLONS (LITERS)	13.4 Gallons (50.7L)	13.4 Gallons (50.7L)	6 Gallons (22.7 L)	7.3 Gallons (27.6L)	7.3 Gallons (27.6L)	7.3 Gallons (27.6L)
GROUND SPEED (APPROX. MPH) (FORWARD/REVERSE)	13 mph/5 mph	13 mph/5 mph	9 mph / 4.5 mph	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph
STARTER	Electric	Electric	Electric	Electric	Electric	Electric
<b>DECK</b>						
DECK MATERIAL	7 ga Steel with .25" Spindle Reinforcement	7 ga Steel with .25" Spindle Reinforcement	7 ga	10 ga w/ .25" Spindle Reinforcement	10 ga w/ .25" Spindle Reinforcement	10 ga w/ .25" Spindle Reinforcement
DECK CONSTRUCTION	Welded	Welded	Welded	Welded	Welded	Welded
NUMBER OF SPINDLES	3	3	3	3	3	3
BLADE TIP SPEED (FPM)	18,500	18,500	18,246	18,000	18,000	18,000
SPINDLE MATERIAL	Cast Iron	Cast Iron	Aluminum	Cast Iron	Cast Iron	Cast Iron
SPINDLE SHAFT	1" Steel	1" Steel	1" Steel	Steel	Steel	Steel
SPINDLE BEARINGS	Tapered Bearing	Tapered Bearing	1" Sealed	Ball Bearing	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Ogura® GT 3.5 Electric Clutch	Ogura® GT 3.5 Electric Clutch	Electric Ogura® GT1A	Electric Ogura® GT1A	Electric Ogura® GT1A	Electric Ogura® GT1A
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Manual	Adjustable Foot Operated	Adjustable Foot Operated	Adjustable Foot Operated
CUTTING WIDTH	60"	54"	52"	60"	52"	48"
CUTTING HEIGHTS	1" - 6"	1" - 6"	1.5" - 4.5"	1" - 5"	1" - 5"	1" - 5"
CUTTING POSITIONS	21	21	7	9	9	9
<b>WHEELS</b>						
FRONT AXLE	Pivoting/Locking	Pivoting/Locking	Rigid	Fixed	Fixed	Fixed
FRONT	Smooth 13" x 6" - 6"	Smooth 13" x 6" - 6"	11" x 4" - 5"	Smooth 13" x 5" - 6"	Smooth 13" x 5" - 6"	Smooth 13" x 5" - 6"
REAR	Turf 24" x 12" - 12"	Turf 24" x 12" - 12"	18" x 8.5" - 8"	Turf 20" x 10" - 10"	Turf 20" x 10" - 10"	Turf 20" x 10" - 10"
<b>FEATURES</b>						
HOOD	N/A	N/A	N/A	N/A	N/A	N/A
HEADLIGHTS	N/A	N/A	N/A	Optional	Optional	Optional
SEAT	High Back w/ Full Suspension & Arm Rests	High Back w/ Full Suspension & Arm Rests	N/A	High Back w/ Seat Springs & Arm Rests	High Back w/ Seat Springs & Arm Rests	High Back w/ Seat Springs & Arm Rests
HOURLY METER	Standard	Standard	Standard	Standard	Standard	Standard
<b>DIMENSIONS</b>						
WEIGHT (LBS)	1201	1173	860	853	832	823
LENGTH	80.5"	80.5"	58"	74.5"	74.5"	71.5"
WIDTH	75" w/chute 61" w/o chute	70" w/chute 55" w/o chute	52.5"	62.8" (w/o chute)	55.5" (w/o chute)	50" (w/o chute)
HEIGHT	74" w/rops up 49" w/rops down	74" w/rops up 49" w/rops down	47.5"	42"	42"	42"
<b>WARRANTY</b>						
MACHINE	2 Year Limited Commercial			3 Year Limited Consumer, 1 Year Limited Commercial		
DECK SHELL & FRAME	Limited Lifetime			5 Year Limited		
SPINDLES	2 Year Limited			3 Year Limited		
<b>ATTACHMENTS &amp; ACCESSORIES</b>						
OPTIONAL	3 Bucket Bagger, Weight Kit		Mulching Kit, Grass Collector	3-Bucket Powered Bagger Kit, Mulching Kit, Trailer Hitch Kit, 36" Poly Roller, 48" Aerator, 48" Dethatcher, 15-Gallon Sprayer, Spreader, Dump Cart, Wheel Covers, Headlight Kit, Suspension Seat Kit, Lawn Striping Kit, Discharge Cover Kit, Engine Guard, FlexTend™ Shoulder Support System, Operator Controlled Chute Baffle, Seat Cover, Mower Cover		

Zoom XL® 54	Zoom XL® 48	Zoom XL® 42	Zoom® 50	Zoom® 42	Zoom® 34
915167	915165	915163	915161	915159	915157
Kawasaki® FR Twin	Kawasaki® FR Twin	Kawasaki® FR Twin	Kohler® Courage Twin	Kohler® Courage Twin	Briggs & Stratton® Single Cylinder
24 hp	24 hp	22 hp	25 hp	22 hp	14.5 hp
726 cc	726 cc	726 cc	725 cc	725 cc	500 cc
Hydro-Gear® ZT-2800 Transaxles	Hydro-Gear® ZT-2800 Transaxles	Hydro-Gear® ZT-2800 Transaxles	Hydro-Gear® EZT Transaxles with 1" Axle Shafts	Hydro-Gear® EZT Transaxles with 1" Axle Shafts	Hydro-Gear® EZT Transaxles with 1" Axle Shafts
3.8 Gallons (14.4L)	3.8 Gallons (14.4L)	3.8 Gallons (14.4L)	2.5 Gallons (9.5L)	2.5 Gallons (9.5L)	2.5 Gallons (9.5L)
6.5 mph /3 mph	6.5 mph /3 mph	6.5 mph /3 mph	6 mph/3 mph	6 mph/3 mph	6 mph/3 mph
Electric	Electric	Electric	Electric	Electric	Electric
10 ga w/ Doubler Plate	10 ga w/ Doubler Plate	10 ga w/ Doubler Plate	12 ga	12 ga	12 ga
Welded	Welded	Welded	Stamped	Stamped	Stamped
3	3	3	3	3	2
16,950	16,800	17,000	17,800	17,000	17,500
Aluminum	Aluminum	Aluminum	Steel	Steel	Steel
1" Steel	1" Steel	1" Steel	Steel	Steel	Steel
1" Sealed	1" Sealed	1" Sealed	Sealed	Sealed	Sealed
Belt	Belt	Belt	Belt	Belt	Belt
Electric Warner®	Electric Warner®	Electric Warner®	Electric Warner®	Electric Warner®	Electric Warner®
Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated
54"	48"	42"	50"	42"	34"
1.5" - 4.5"	1.5" - 4.5"	1.5" - 4.5"	1" - 4"	1" - 4"	1" - 4"
7	7	7	7	7	7
Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
11" x 4"	11" x 4"	11" x 4"	11" x 4"	11" x 4"	11" x 4"
20" x 10"	20" x 10"	20" x 8"	18" x 9.5"	18" x 8.5"	18" x 6.5"
Standard	Standard	Standard	Standard	Standard	Standard
Optional	Optional	Optional	N/A	N/A	N/A
High Back w/ Seat Springs, Lever Adjust & Arm Rests	High Back w/ Seat Springs, Lever Adjust & Arm Rests	High Back w/ Seat Springs, Lever Adjust & Arm Rests	High Back w/ Seat Springs	High Back w/ Seat Springs	Mid Back w/ Seat Springs
Standard	Standard	Standard	N/A	N/A	N/A
645	630	615	475	440	425
69"	69"	69"	64"	64"	64"
64"	58"	52"	62"	54"	42"
42"	42"	42"	43"	43"	37"
3 Year Limited Consumer			3 Year Limited Consumer		
5 Year Limited			5 Year Limited		
N/A			N/A		
3-Bucket Powered Bagger Kit, Mulching Kit, Trailer Hitch Kit, 36" Poly Roller, 48" Aerator, 48" Dethatcher, 15-Gallon Sprayer, Spreader, Dump Cart, Wheel Covers, Sun Shade, Headlight Kit, 54" Snow Blade, Two-Stage Snowblower, FlexTend™ Shoulder Support System, Seat Cover, Mower Cover, Engine Guard			2-Bucket Non-Powered Bagger Kit, Mulching Kit, Trailer Hitch Kit (Standard on 42" & 50" models), 36" Poly Roller, 48" Aerator, 48" Dethatcher, 15-Gallon Sprayer, Spreader, Dump Cart, Wheel Covers, FlexTend™ Shoulder Support System, Seat Cover, Mower Cover		

<b>PRODUCT NAME</b>	<b>AMP Rider</b>
<b>MODEL NUMBER</b>	91600200
<b>MOTORS</b>	Brushless DC Motors
<b>HORSEPOWER*</b>	4 HP Traction Drive and (2) 1.7 hp Deck Blade Drive
<b>DRIVE SYSTEM</b>	Hydrostatic Transaxle with 3/4" axles
<b>BATTERY CAPACITY VOLTS &amp; AMP HOUR RATING</b>	48V 75 AH battery system comprised of (5) 48V 15 AH sub packs.
<b>GROUND SPEED (APPROX. MPH) (FORWARD/REVERSE)</b>	5 mph/2.5 mph
<b>RUN TIME (NORMAL OPERATION)</b>	50-75 mins.
<b>CHARGE TIME -5AH CHARGER</b>	12-16 hrs
<b>CHARGE TIME-20AH CHARGER</b>	4-5 hrs
<b>DECK</b>	
<b>DECK MATERIAL</b>	12 ga
<b>DECK CONSTRUCTION</b>	Stamped
<b>NUMBER OF SPINDLES</b>	2
<b>BLADE TIP SPEED (FPM)</b>	16,000
<b>SPINDLE MATERIAL</b>	Steel Motor Shaft
<b>SPINDLE SHAFT</b>	17 mm Dia. Steel Motor Shaft
<b>SPINDLE BEARINGS</b>	17 mm Sealed
<b>DECK DRIVE</b>	2 (1.7 HP) Electric Motors
<b>DECK ENGAGEMENT</b>	Electric - Blade Mounted Directly to Motor Shaft.
<b>DECK LIFT SYSTEM</b>	Hand Operated
<b>CUTTING WIDTH</b>	34"
<b>CUTTING HEIGHTS</b>	1.5"- 4.5"
<b>CUTTING POSITIONS</b>	13
<b>WHEELS</b>	
<b>FRONT AXLE</b>	Floating
<b>FRONT</b>	11" x 4"
<b>REAR</b>	18" x 6.5"
<b>FEATURES</b>	
<b>HOOD</b>	Standard
<b>HEADLIGHTS</b>	N/A
<b>SEAT</b>	Mid Back w/Seat Springs
<b>HOOR METER</b>	N/A
<b>DIMENSIONS</b>	
<b>WEIGHT (LBS)</b>	530
<b>LENGTH</b>	61"
<b>WIDTH</b>	44.5 "
<b>HEIGHT</b>	41.25 "
<b>WARRANTY</b>	
<b>WARRANTY (EXCEPT BATTERIES)</b>	3 Year Limited Consumer
<b>BATTERY WARRANTY</b>	100% first year, pro rated second year
<b>ATTACHMENTS &amp; ACCESSORIES</b>	
<b>OPTIONAL</b>	48V 20A Charger, Bagger Kit, Mulching Kit

<b>PRODUCT NAME</b>	<b>Lawn Tractor 42</b>	<b>Lawn Tractor 46</b>	<b>Garden Tractor 54</b>
<b>MODEL NUMBER</b>	936051	936053	936055
<b>ENGINE</b>	Kohler® Courage Single	Briggs & Stratton® V-Twin	Kohler® Courage V-Twin
<b>HORSEPOWER*</b>	19 hp	22 hp	25 hp
<b>DISPLACEMENT (cc)</b>	597 cc	656 cc	725 cc
<b>DRIVE SYSTEM</b>	Hydrostatic Fender Shift Lever	Hydrostatic Fender Shift Lever	Hydrostatic Foot Pedal
<b>FUEL CAPACITY GALLONS (LITERS)</b>	2.5 Gallons (9.5L)	2.5 Gallons (9.5L)	4.0 Gallons (15.2L)
<b>GROUND SPEED (APPROX. MPH) (FORWARD/REVERSE)</b>	5.5 mph/2.5 mph	5.5 mph/2.5 mph	5.5 mph/2.5 mph
<b>STARTER</b>	Electric (Bendix)	Electric (Bendix)	Electric (Bendix)
<b>DECK</b>			
<b>DECK MATERIAL</b>	12 ga	12 ga	10 ga
<b>DECK CONSTRUCTION</b>	Stamped	Stamped	Stamped
<b>NUMBER OF SPINDLES</b>	2	2	3
<b>BLADE TIP SPEED (FPM)</b>	19,000 (max)	19,000 (max)	19,000 (max)
<b>SPINDLE MATERIAL</b>	Cast Aluminum	Cast Aluminum	Cast Aluminum
<b>SPINDLE SHAFT</b>	Steel	Steel	Steel
<b>SPINDLE BEARINGS</b>	Sealed	Sealed	Greaseable
<b>DECK DRIVE</b>	Belt	Belt	Belt
<b>DECK ENGAGEMENT</b>	PTO Electric	PTO Electric	PTO Electric
<b>DECK LIFT SYSTEM</b>	Manual, Spring Assist	Manual, Spring Assist	Manual, Spring Assist
<b>CUTTING WIDTH</b>	42"	46"	54"
<b>CUTTING HEIGHTS</b>	1.5" - 4"	1.5" - 4"	1.5" - 4"
<b>CUTTING POSITIONS</b>	6	6	7
<b>TURNING RADIUS</b>	16"	16"	18"
<b>WHEELS</b>			
<b>FRONT AXLE</b>	Steel	Steel	Cast Iron
<b>FRONT</b>	15" x 6" - 6" Turf Saver	15" x 6" - 6" Turf Saver	16" x 6.5" - 6" Turf Saver
<b>REAR</b>	20" x 8" - 8" Turf Saver	20" x 8" - 8" Turf Saver	23" x 10.5" - 12" Turf Saver
<b>FEATURES</b>			
<b>HOOD</b>	Stealth	Stealth	Stealth
<b>HEADLIGHTS</b>	Yes	Yes	Yes
<b>SEAT</b>	High Back 15", Slide	High Back 15", Slide	High Back 15", Slide
<b>HOOR METER</b>	N/A	N/A	N/A
<b>DIMENSIONS</b>			
<b>WEIGHT (LBS)</b>	472	493	698
<b>LENGTH</b>	72.75"	72.75"	73.75"
<b>WIDTH</b>	45"	49.5"	58.5"
<b>HEIGHT</b>	46"	46"	47"
<b>WARRANTY</b>			
<b>MACHINE</b>	2 Year Limited Consumer		
<b>ATTACHMENTS &amp; ACCESSORIES</b>			
<b>OPTIONAL</b>	Bagger Kit, Mulching Kit		

PRODUCT NAME	Wide Area Walk 34	Pro21	Classic LM 21	Classic LM21 S	Classic LM21 SW	Value Walk Behind	Value Walk Behind
MODEL NUMBER	911413	911271	911160	911183	911184	961360	961464
ENGINE	Briggs & Stratton®	Kawasaki® FJ180V	Kohler® XT-7	Kawasaki® FJ180V	Kawasaki® FJ180V	Kohler® XT-6	Honda® GCV 160
HORSEPOWER*	14.5 hp	6 hp	4.5 hp	6 hp	6 hp	3.5 hp	5.5 hp
DISPLACEMENT (cc)	500 cc	179 cc	173 cc	179 cc	179 cc	149 cc	160 cc
DRIVE SYSTEM	Variable Speed Belt Drive	Variable Speed Belt Drive	Push	Infi-Speed® Variable Speed Drive	Infi-Speed® Variable Speed Drive	Push	FWD Self Propelled
FUEL CAPACITY GALLONS (LITERS)	2.5 Gallons (9.5L)	0.53 Gallon (2L)	0.37 Gallon (1.4L)	0.53 Gallon (2L)	0.53 Gallon (2L)	0.24 Gallon (1L)	0.37 Gallon (1.4L)
GROUND SPEED (APPROX. MPH) (FORWARD/REVERSE)	3.5 mph Forward/2 mph Reverse	3.75 mph	N/A	4 mph	4 mph	N/A	N/A
STARTER	Electric Start	Recoil	Recoil	Recoil	Recoil	Manual Pull	Manual Pull
<b>DECK</b>							
DECK MATERIAL	12 ga	14 ga	14 ga	14 ga	14 ga	12 ga	12 ga
DECK CONSTRUCTION	Stamped	Stamped	Stamped	Stamped	Stamped	Stamped	Stamped
NUMBER OF SPINDLES	2	1	1	1	1	1	1
BLADE TIP SPEED (FPM)	17,969	18,000	18,000	18,000	18,000	19,000	19,000
SPINDLE MATERIAL	Steel	Steel	Steel	Steel	Steel	Cast Aluminum	Cast Aluminum
SPINDLE SHAFT	5/8"	7/8"	7/8"	7/8"	7/8"	NA	NA
SPINDLE BEARINGS	Sealed Ball	Sealed Ball	Sealed Ball	Sealed Ball	Sealed Ball	NA	NA
DECK DRIVE	Belt	Direct	Direct	Direct	Direct	NA	NA
DECK ENGAGEMENT	PTO Lever	NA	NA	NA	NA	NA	NA
DECK LIFT SYSTEM	Manual	Manual	Manual	Manual	Manual	Manual	Manual
CUTTING WIDTH	34"	21"	21"	21"	21"	21"	21"
CUTTING HEIGHTS	1.75" - 3.5"	1.5" - 3.6"	1" - 3.25"	1" - 3.25"	1" - 3.25"	1.25" - 3.42"	1.25" - 3.42"
CUTTING POSITIONS	7	6	6	6	6	5	5
<b>WHEELS</b>							
FRONT AXLE	Swivel	Fixed	Fixed	Fixed	Swivel	Fixed	Fixed
FRONT	8"	8"	7.5"	7.5"	7.5"	7"	8"
REAR	13"	8"	10.5"	10.5"	10.5"	12"	8"
<b>DIMENSIONS</b>							
WEIGHT (LBS)	280	125	100	104	121	85	85
LENGTH	67"	62.5"	61.5"	61.5"	61.5"	36.25"	36.25"
WIDTH	42"	23.5"	23"	23"	23"	21"	21"
HEIGHT	38"	40.6"	38"	38"	38"	25.25"	25.25"
<b>WARRANTY</b>							
MACHINE	3 Year Limited Consumer	3 Year Limited Consumer, 1 Year Limited Commercial	3 Year Limited Consumer	3 Year Limited Consumer	3 Year Limited Consumer	2 Year Limited Consumer	2 Year Limited Consumer
<b>ATTACHMENTS &amp; ACCESSORIES</b>							
BAGGER KIT	Available	Standard	Standard	Standard	Standard	Standard	Standard
MULCHING KIT	Available	Standard	Standard	Standard	Standard	Integrated	Integrated
LEAF SHREDDER	N/A	Available	Available	Available	Available	N/A	N/A
DETHATCHER	N/A	N/A	Available	Available	Available	N/A	N/A

PRODUCT NAME	Professional Walk 36GR	Professional Walk 48GR
MODEL NUMBER	988811	988812
ENGINE	Kawasaki® FS481V	Kawasaki® FS481V
HORSEPOWER*	16 hp	16 hp
DISPLACEMENT (cc)	603 cc	603 cc
DRIVE SYSTEM	Peerless Gear Drive	Peerless Gear Drive
FUEL CAPACITY - Gallons (LITERS)	6.6 Gallon (24.9L)	6.6 Gallon (24.9L)
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	5.4 mph / Reverse Assist	5.4 mph / Reverse Assist
STARTER	Recoil	Recoil
<b>DECK</b>		
DECK MATERIAL	7 ga	7 ga
DECK CONSTRUCTION	Welded	Welded
NUMBER OF SPINDLES	2	3
BLADE TIP SPEED (FPM)	18,152	18,220
SPINDLE HOUSING MATERIAL	Aluminum	Aluminum
SPINDLE SHAFT	1" Steel	1" Steel
SPINDLE BEARINGS	1" Sealed	1" Sealed
DECK DRIVE	Belt	Belt
DECK ENGAGEMENT	Electric Clutch	Electric Clutch
DECK LIFT SYSTEM	Manual	Manual
CUTTING WIDTH	36"	48"
CUTTING HEIGHTS	1.5"- 4"	1.5"- 4"
CUTTING POSITIONS (1/4" INCREMENTS)	10	10
<b>WHEELS</b>		
FRONT AXLE	Swivel	Swivel
FRONT	3.5	3.5
REAR	6.5	6.5
<b>DIMENSIONS</b>		
WEIGHT (LBS)	481	548
LENGTH	75.6"	70.9"
WIDTH	48.4"	60.8"
HEIGHT	41.9"	41.9"
<b>WARRANTY</b>		
MACHINE	2 Year Limited Commercial	
DECK SHELL & FRAME	Limited Lifetime Deck Shell & Frame	
SPINDLES	2 Year Limited Spindle	
<b>ATTACHMENTS &amp; ACCESSORIES</b>		
OPTIONAL	Mulching Kit, Grass Collector	

PRODUCT NAME	27- Ton Log Splitter	34- Ton Log Splitter
MODEL NUMBER	917001	917002
ENGINE	Subaru®	Subaru®
DISPLACEMENT (cc)	169 cc	211 cc
STARTING SYSTEM	Recoil	Recoil
STARTING SYSTEM	.95 Gallon (3.6L)	.95 Gallon (3.6L)
LOG CAPACITY	25"	25"
HYDRAULIC CAPACITY	4.5 Gallon(17L)	4.5 Gallon(17L)
SPLITTING FORCE	27 Ton	34 Ton
CYLINDER PISTON SIZE	4.5" Bore	5" Bore
CYLINDER ROD SIZE	1.75"	1.75"
CYLINDER STROKE	24"	24"
CYLINDER CONSTRUCTION	Welded -Trunnion Mount	Welded -Trunnion Mount
RESERVOIR SIZE	3.5 Gallons	3.5 Gallons
PUMP SIZE	11 GPM	13 GPM
CYLINDER CYCLE TIME	16 Seconds	18 Seconds
TIRE SIZE	4.8" / 4" x 8"	4.8" / 4" x 8"
HITCH COUPLER	2"	2"
MAX TOWING SPEED	45 mph / 72.4 kmh	45 mph / 72.4 kmh
<b>DIMENSIONS</b>		
WEIGHT (LBS)	500	525
LENGTH (HORIZONTAL POSITION)	86.25"	86.25"
LENGTH (VERTICAL POSITION)	83.75"	83.75"
WIDTH	38.25"	38.25"
HEIGHT (HORIZONTAL POSITION)	46.50"	46.50"
HEIGHT (VERTICAL POSITION)	64.75"	64.75"
<b>WARRANTY</b>		
MACHINE	3 Year Limited Consumer, 90-Day Limited Commercial	3 Year Limited Consumer, 90-Day Limited Commercial
<b>FEATURES</b>		
SPLITTING ORIENTATION	Vertical or Horizontal	
2-STAGE HYDRAULIC PUMP	Yes	
WHEEL FENDERS	Yes	
SAFETY CHAINS	Yes	
LEFT OR RIGHT HAND OPERATION	Yes	
<b>ATTACHMENTS &amp; ACCESSORIES</b>		
OPTIONAL	Work Table, Trailer Lights, License Plate Holder, Engine Cover, Log Cradle, Lift Handle, Muffler Guard	

PRODUCT NAME	
MODEL NUMBER	
ENGINE	
HORSEPOWER*	
DISPLACEMENT (cc)	
STARTING SYSTEM	
FUEL TANK CAPACITY	
BRUSH WIDTH	
BRUSH ROTATION ANGLE	
BRUSH ROTATION CONTROL	
INTERLOCK CONTROL	
TIRE SIZE	
TIRE TYPE	
AXLE SYSTEM	
SPEEDS: FORWARD/ REVERSE	
BRUSH DIAMETER	
<b>DIMENSIONS</b>	
WEIGHT (LBS)	
LENGTH	
WIDTH	
HEIGHT	
<b>WARRANTY</b>	
MACHINE	
<b>FEATURES</b>	
ELECTRIC START	
HALOGEN HEADLIGHTS	
<b>ATTACHMENTS &amp; ACCESSORIES</b>	
OPTIONAL	

Power Brush 28	Power Brush 36
921025	926045
Subaru®	Subaru®
6 hp	9 hp
169 cc	265 cc
120V/Recoil	120V/Recoil
.95 Gallon (3.6L)	1.6 Gallon (6.1L)
28"	36"
40°	40°
Remote Trigger	Remote Trigger
Standard	Standard
15" x 5"	16" x 6.5"
Directional Snow Tread	Directional Snow Tread
Automatic Traction Control	Automatic Traction Control
6 Forward/2 Reverse	6 Forward/2 Reverse
18"	25"
230	325
65"	72"
34"	44"
44"	43"
3 Year Limited Consumer, 90-Day Limited Commercial	3 Year Limited Consumer, 1 Year Limited Commercial
Standard	
N/A	Standard
ACCESSORIES	
Snow Cab, Turf Caster Kit, MeltBuddy™	Debris Deflector, Snow Cab, Turf Wheels, MeltBuddy™

PRODUCT NAME	Front Tine Tiller	Rear Tine Tiller
<b>MODEL NUMBER</b>	902032	901028
<b>ENGINE</b>	Subaru®	Subaru®
<b>HORSEPOWER*</b>	6 hp	6 hp
<b>ENGINE DISPLACEMENT (cc)</b>	169 cc	169 cc
<b>DRIVE SYSTEM</b>	Roller Chain	Chain / Gear
<b>FUEL CAPACITY GALLONS (LITERS)</b>	0.89 Gallon (3.4L)	0.89 Gallon (3.4L)
<b>TINE SPEED</b>	118 rpm	190 rpm
<b>STARTER</b>	Pull	Pull
DECK		
<b>TILLING WIDTH</b>	24"/22"/12"	17"
<b>TINE DIAMETER</b>	12"	13"
<b>TILLING DEPTH</b>	6"	6.5"
<b>HANDLE</b>	Foldable	Adjustable
WHEELS		
<b>TIRE SIZE</b>	1.75" x 8" Semi -Pneumatic	13" x 5" - 6" Pneumatic
DIMENSIONS		
<b>WEIGHT (LBS)</b>	115	230
<b>LENGTH (INCHES)</b>	27.5"	48"
<b>WIDTH (INCHES)</b>	25"	24.5"
<b>HEIGHT (INCHES)</b>	33.5"	34.5"
WARRANTY		
<b>MACHINE</b>	2 Year Limited Consumer	2 Year Limited Consumer
FEATURES		
	7 Position, Spring Loaded, Depth and Drag Stake	Dual Rotating Tines, Power Forward and Reverse, Deep Tread Tires

PRODUCT NAME	Lawn Edger	String Trimmer
<b>MODEL NUMBER</b>	986103	946152
<b>ENGINE</b>	LCT Overhead Cam	Kohler® XT-7
<b>HORSEPOWER*</b>	N/A	4.5 hp
<b>DISPLACEMENT (cc)</b>	136 cc	173 cc
<b>STARTING SYSTEM</b>	Recoil	Recoil
<b>DRIVE SYSTEM</b>	Push	Push
<b>FUEL CAPACITY</b>	0.71 Gallon (2.6L)	0.37 Gallon(1.4L)
DECK		
<b>DECK MATERIAL</b>	12 ga	14 ga
<b>DECK CONSTRUCTION</b>	Formed	Stamped
<b>NUMBER OF SPINDLES</b>	1	1
<b>BLADE DIAMETER</b>	9 Inch	N/A
<b>SPINDLE MATERIAL</b>	Steel	N/A
<b>SPINDLE SHAFT</b>	1/2" Dia. Steel	N/A
<b>SPINDLE BEARINGS</b>	Sealed	N/A
<b>DECK DRIVE</b>	Belt	Belt
<b>CUT ANGLE</b>	110 Degrees	N/A
<b>CUT POSITIONS</b>	4	4
<b>CUTTING WIDTH</b>	N/A	22" w/ 15° Swivel to the Left and Right
<b>CUTTING HEIGHTS</b>	N/A	1.25" - 4.25"
<b>OPERATOR SAFETY LEVER</b>	Yes	N/A
WHEELS		
<b>WHEEL DIAMETER</b>	8"	N/A
<b>WHEEL BEARINGS</b>	Yes	N/A
<b>DROP WHEEL FOR CURB</b>	Yes	N/A
<b>FRONT AXLE</b>	Laterally Adjustable	N/A
<b>FRONT</b>	1.75" x 7.5"	N/A
<b>REAR</b>	1.75" x 7.5"	14"
DIMENSIONS		
<b>WEIGHT (LBS)</b>	72	83
<b>LENGTH</b>	44.75"	58"
<b>WIDTH</b>	19.75"	22"
<b>HEIGHT</b>	38"	41"
WARRANTY		
<b>MACHINE</b>	3 Year Limited Consumer	3 Year Limited Consumer

BE SURE TO ASK YOUR LOCAL DEALER ABOUT THESE OUTSTANDING ARIENS SNOW PRODUCTS.

# THE KING OF SNOW



Durability. Reliability. Unrelenting power. That's what you'll find in the entire Ariens® Sno-Thro® lineup. Every machine is subjected to the most rigorous testing and trial conditions imaginable. So when winter brings on the worst, bring on the best—**The King of Snow**—built to last a lifetime. Consult with your Ariens dealer about selecting the Sno-Thro model that's right for you.



[WWW.ARIENS.COM](http://WWW.ARIENS.COM)

Phone: 920.756.4688  
Email: [info@ariens.com](mailto:info@ariens.com)