

PLATINUM SERIES



URNS BLANKETS OF SNOW INTO TATTERED RAGS.

When you get behind your Platinum, you'll want to keep going – driveway after driveway. These units were built for high-volume workloads, hence their standard hand-warmers and Super High Output (SHO) impellers. The Platinum Series is loaded with plenty of other features sure to fit your snow removal needs.

My favorite thing about my Ariens is the built-in handwarmers. I go up and down my entire block, the neighbors love me.

*– Michael H.
Superior, WI*

AUTO-TURN™ STEERING

Effortless, zero-degree turning radius.

AUGER

Our 14" serrated auger chews up the snow.

ENGINE

Choose from 3 different types of Ariens engines.

SUPER HIGH OUTPUT IMPELLER (SHO)

Move through heavy, wet snow with ease with our exclusive SHO technology.

DUAL-BELT DRIVE

Exclusive to Ariens, delivers maximum power through tough conditions, plus extended belt life.

HAND WARMERS

Stay warm and comfortable with our premium hand warmers.

ELECTRIC CHUTE CONTROL AVAILABLE

A convenient thumb-controlled joystick makes chute turns quick and effortless with full rotations taking only 1.5 seconds.

EFI ENGINE AVAILABLE

Our Electronic Fuel Injection engine is easy starting, less maintenance, improved efficiency making it ideal for high altitude snow removal.

3 YEAR
LTD. RESIDENTIAL
WARRANTY

90 DAY
LTD. COMMERCIAL
WARRANTY

PRODUCT SPECIFICATIONS

RAPIDTRAK



| DESIGNATION | PLATINUM 24 SHO | PLATINUM 24 SHO EFI GREAT LAKES EDITION™ | PLATINUM 28 SHO RAPIDTRAK® | PLATINUM 30 SHO | PLATINUM 24 SHO 90TH ANNIVERSARY EDITION |
|-------------------------|--|--|--|---|---|
| MODEL # | 921074 | 921066 | 921073 | 921075 | 921933 |
| STAGE TYPE | TWO STAGE | TWO STAGE | TWO STAGE | TWO STAGE | TWO STAGE |
| ENGINE POWER | 389CC | 369CC EFI | 389CC | 420CC | 369CC |
| ENGINE BRAND | ARIENS AX | ARIENS AX | ARIENS AX | ARIENS AX | TECUMSEH POWER SNOW KING |
| STARTING SYSTEM | 120V/RECOIL | 120V/RECOIL | 120V/RECOIL | 120V/RECOIL | 120V/RECOIL |
| CLEARING WIDTH | 24 IN (60.1 CM) | 24 IN (60.1 CM) | 28 IN (71.2 CM) | 30 IN (76.2 CM) | 24 IN (60.1 CM) |
| HOUSING HEIGHT | 21 IN (53.3 CM) | 21 IN (53.3 CM) | 21 IN (53.3 CM) | 21 IN (53.3 CM) | 21 IN (53.3 CM) |
| THROWING DISTANCE | 3 - 55 FT (.9 - 16.7 M) | 3 - 55 FT (.9 - 16.7 M) | 3 - 55 FT (.9 - 16.7 M) | 3 - 55 FT (.9 - 16.7 M) | 3 - 55 FT (.9 - 16.7 M) |
| CHUTE TURNING RADIUS | 200° | 200° | 200° | 200° | 200° |
| CHUTE ROTATION | QUICK TURN™ | ELECTRIC JOYSTICK | QUICK TURN™ | QUICK TURN™ | QUICK TURN™ |
| DEFLECTOR CONTROL | REMOTE | ELECTRIC | REMOTE | REMOTE | REMOTE |
| HEADLIGHT | LED | LED HEADLIGHT & LIGHTBAR | LED | LED | LED |
| TIRE SIZE | 16 X 4.8 IN (41 X 12 CM) | 16 X 4.8 IN (41 X 12 CM) | 5.5 IN WIDE TRACK (14 CM) | 16 X 4.8 IN (41 X 12 CM) | 16 X 4.8 IN (41 X 12 CM) |
| TIRE TYPE | DIRECTIONAL SNOW TREAD | DIRECTIONAL SNOW TREAD | DIRECTIONAL SNOW TRACK | DIRECTIONAL SNOW TREAD | DIRECTIONAL SNOW TREAD |
| STEERING | AUTO-TURN | AUTO-TURN | AUTO-TURN | AUTO-TURN | AUTO-TURN |
| DRIVE TYPE | DISC-O-MATIC | DISC-O-MATIC | DISC-O-MATIC | DISC-O-MATIC | DISC-O-MATIC |
| SPEEDS | 6 FORWARD 2 REVERSE | 6 FORWARD 2 REVERSE | 6 FORWARD 2 REVERSE | 6 FORWARD 2 REVERSE | 6 FORWARD 2 REVERSE |
| GEAR CASE | CAST IRON | CAST IRON | CAST IRON | CAST IRON | CAST IRON |
| GEAR CASE WARRANTY | 5YR RES, 1YR COMM | 5 YR RES, 1YR COMM | 5YR RES, 1YR COMM | 5YR RES, 1YR COMM | 5YR RES, 1YR COMM |
| IMPELLER PROFILE | STEEL 3 BLADE | STEEL 3 BLADE | STEEL 3 BLADE | STEEL 3 BLADE | STEEL 3 BLADE |
| IMPELLER DIAMETER | 14 IN (35.6 CM) | 14 IN (35.6 CM) | 14 IN (35.6 CM) | 14 IN (35.6 CM) | 14 IN (35.6 CM) |
| AUGER DIAMETER | 14 IN (35.6 CM) | 14 IN (35.6 CM) | 14 IN (35.6 CM) | 14 IN (35.6 CM) | 14 IN (35.6 CM) |
| AUGER TYPE | STEEL SERRATED | STEEL SERRATED | STEEL SERRATED | STEEL SERRATED | STEEL SERRATED |
| SKID SHOES | POLY REVERSIBLE | POLY REVERSIBLE | POLY REVERSIBLE | POLY REVERSIBLE | POLY REVERSIBLE |
| SCRAPER BAR | STEEL ADJUSTABLE | STEEL ADJUSTABLE | STEEL ADJUSTABLE | STEEL ADJUSTABLE | STEEL ADJUSTABLE |
| PRODUCT WARRANTY | 3YR RES, 90DAY COMM | 3YR RES, 90DAY COMM | 3YR RES, 90DAY COMM | 3YR RES, 90DAY COMM | 3YR RES, 90DAY COMM |
| LENGTH | 58.3 IN (148.1 CM) | 58.3 IN (148.1 CM) | 60.3 IN (153.2 CM) | 58.3 IN (148.1 CM) | 58.3 IN (148.1 CM) |
| WIDTH | 26.4 IN (67.1 CM) | 26.4 IN (67.1 CM) | 30.2 IN (76.7 CM) | 32.4 IN (82.3 CM) | 26.4 IN (67.1 CM) |
| HEIGHT | 45.9 IN (116.6 CM) | 45.9 IN (116.6 CM) | 46.6 IN (118.4 CM) | 45.9 IN (116.6 CM) | 45.9 IN (116.6 CM) |
| WEIGHT | 286 LBS (129.7 KG) | 286 LBS (129.7 KG) | 331 LBS (150.1 KG) | 294 LBS (133.3 KG) | 286 LBS (129.7 KG) |
| ACCESSORIES AT A GLANCE | TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, SNO-THRO CAB, SNO-THRO COVER | TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, SNO-THRO CAB, SNO-THRO COVER | FRONT WEIGHT KIT, SNO-THRO CAB, SNO-THRO COVER | TIRE CHAINS, DRIFT CUTTER KIT, FRONT WEIGHT KIT, SNO-THRO CAB, SNO-THRO COVER | TIRE CHAINS, DRIFT CUTTER KIT, FRONT WEIGHT KIT, SNO-THRO CAB, SNO-THRO COVER |



Registered trademark and ™ trademark of AriensCo. Kawasaki®, Kohler® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2024 AriensCo. All rights reserved. 0924

VISIT [ARIENS.COM](https://www.ariens.com) FOR DETAILS

AN **ARIENS|CO** BRAND