



INTRODUCING THE FIRST SNO-THRO

EFI TECHNOLOGY.

KNOWLEDGE IS POWER

Ariens AX EZ-Launch™ EFI engine features an electronic governor to eliminate speed loss, delivering consistent throwing performance and an ultra-quiet idle.



A completely sealed unit, the EFI fuel system eliminates maintenance costs. It won't gum up in the off-season, so you can pack it away with plenty of peace of mind.



Prepare for launch.

If you're like us, you look forward to the winter forecast. You peer out the window in anticipation of precipitation.

And this year, there's even more reason to look forward to the season. Because now you've got a new trick for Old Man Winter – A new toy to take out to the powdery playground.

There's excitement in the air and an all new Ariens AX EZ-Launch EFI engine in your garage.

SO LET'S GET STARTED.

One turn of the key. One pull to start. No matter what the conditions. The Ariens AX EZ-Launch starts easier, sips less fuel and throws with more consistent power.

It's one more reason to love the winter season. And it's only found on Ariens Sno-Thros®.



DESIGNATION	PLATINUM SHO 24 EFI	PROFESSIONAL 28 HYDRO EFI	HYDRO PRO 28 EFI TRACK
MODEL#	921327	926336	926337
STAGE TYPE	Two Stage	Two Stage	Two Stage
ENGINE POWER	369cc EFI/E-Gov (17 ft/lbs)	420cc EFI/E-Gov (21 ft/lbs)	420cc EFI/E-Gov (21 ft/lbs)
ENGINE BRAND	Ariens EZ-Launch EFI	Ariens EZ-Launch EFI	Ariens EZ-Launch EFI
STARTING SYSTEM	240V/Recoil	240V/Recoil	240V/Recoil
CLEARING WIDTH	24 in (60.1 cm)	28 in (71.2 cm)	28 in (71.2 cm)
HOUSING HEIGHT	21 in (53.3 cm)	23.5 in (59.7 cm)	23.5 in (59.7 cm)
T H R O W I N G D I S T A N C E	3 ft - 55 ft (.9-16.7 m)	3 ft - 60 ft (.9-18.2 m)	3 ft - 60 ft (.9-18.2 m)
C H U T E T U R N I N G R A D I U S	200°	200°	200°
C H U T E R O T A T I O N	QuickTurn	Quick Turn	QuickTurn
DEFLECTOR CONTROL	Remote	Remote	Remote
TIRE SIZE	16 x 4.8 in (41 x 12 cm)	16 in x 4.8 in (41 x 12 cm)	5.5" W
TIRE TYPE	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread Track
STEERING	Auto-Turn	Auto-Turn	Auto-Turn
DRIVE TYPE	Disc-O-Matic	Hydrostatic	Hydrostatic
SPEEDS	6 Forward/ 2 Reverse	Variable	Variable
GEAR CASE	Cast Iron	Cast Iron	Cast Iron
GEAR CASE WARRANTY	5yr Cons, 1yr Comm	5yr Cons, 1yr Comm	5yr Cons, 1yr Comm
IM PELLER PROFILE	Steel 3 Blade	Steel 3 Blade	Steel 3 Blade
I M P E L L E R D I A M E T E R	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)
AUGER DIAMETER	14 in (35.6 cm)	16 in (40.6 cm)	16 in (40.6 cm)
AUGER TYPE	Steel Serrated	Steel Serrated	Steel Serrated
SKID SHOES	Steel Reversible	Commercial Skids	Commercial Skids
SCRAPER BAR	Steel Adjustable	Steel Adjustable	Steel Adjustable
P R O D U C T W A R R A N T Y	3yr Cons, 90 day Comm	3yr Cons, 1 yr Comm	3yr Cons, 1 yr Comm
LENGTH	58.3 in (148.1 cm)	60.3 (153.2 cm)	60.6 in (153.9 cm)
WIDTH	26.4 in (67.1 cm)	30.2 in (76.7 cm)	30.2 in (76.7 cm)
HEIGHT	45.9 in (116.6 cm)	46.6 in (118.4 cm)	45.9 in (116.6 cm)
WEIGHT	273 lbs (123.8 kg)	350.6 lbs (159 kg)	348.7 lb (158.2 kg)
FEATURES AT A GLANCE	Halogen Headlight, Handwarmers, Remote Deflector, Electric Start, Drift Cutters (optional), One Hand Interlock	Halogen Headlight, Handwarmers, Remote Deflector, Electric Start, Drift Cutters, One Hand Interlock	Halogen Headlight, Handwarmers, Remote Deflector, Electric Start, Drift Cutters, Track Drive, One Hand Interlock

©2017 Ariens Company. All rights reserved. ® Registered trademark and TM trademark of Ariens Company and Hyrdro-Gear are registered trademarks of their respective companies. Sno-Thro unit specifications and features are subject to change without notice. Photos are a representation, actual product may differ.



